



[CLICK TO WATCH VIDEO](#)

InstaVC 4K-120 Auto Frame

InstaVC 4K Auto Frame Camera delivers high definition experience of video conference at an optimized bandwidth. It automatically Zooms and perfectly frames all meeting participants. Supports 4k@30fps with inbuilt stereo high gain microphones. It supports ePTZ(pan, Tilt and Zoom), comes along with remote to control. It comes with FOV of 120 Degree. The integrated compact design houses powerful 4K camera, microphone to host High definition video conference.

Product Features

- 8X Digital Zoom
- Ultra 4K
- FOV 120°
- Built in Microphone
- Support ePTZ
- Support WDR
- 2D,3D digital noise reduction
- Supports Backlight Compensation
- Plug & Play



[CLICK TO VISIT WEBPAGE](#)

Specifications

InstaVC 4K-120 Auto Frame

Camera

Digital Zoom	: 8X
Video System(HDMI)	: 4K@30fps/25fps, 1080P@30/25fps, 1080I@60/50fps, 720P@60/50fps
Sensor	: 1/2.5", CMOS, Effective Pixel: 8.51M
Scanning Mode	: Progressive
Lens Mount	: M12
Lens	: Focus: f=2.8mm, FOV: 120°
Autofocus	: Support
Minimal Illumination	: 0.05 Lux @ (F1.8, AGC ON)
Shutter	: 1/30s ~ 1/10000s
White Balance	: Auto, Indoor, Outdoor, One Push, Manual
Camera bracket	: Bracket with damper
Digital Noise Reduction	: 2D,3D digital noise reduction
Backlight Compensation	: Support

USB Features

Operating System	: Windows® 7 (1080P and under only), Windows 8.1, Windows 10 or higher mac OS™ 10.10 or higher Google™ Chrome book™ Version 29.0.1547.70 or higher Linux
Hardware Requirement	: 2.4 GHz Intel® Core 2 Duo processor or higher 2 GB RAM or more USB 2.0 port (USB 3.0 required for 4K)
Color System / Compression	: H.265 / H.264 / MJPEG / YUY2
Resolution	: 4K, 1080P, 720P, 960x540P, 640x360P, 320x240P
Frame rate	: 30fps, 25fps, 24fps, 20fps, 15fps, 10fps, 7.5fps, 5fps
USB Video Communication Protocol	: UVC v1.0/v1.1
UVC PTZ	: Support(EPTZ)

Input / Output Interface

USB Interface	: 1xUSB 3.0: Type B, female
HDMI Interface	: 1xHDMI: Version 1.4

General specification

Input Voltage	: 5V (USB power supply)
Current Consumption	: L1A
Operating Temperature	: -10°C ~ 40°C (14°F ~ 104°F)
Storage Temperature	: -40°C ~ 60°C (-40°F ~ 140°F)
Power Consumption	: 3.5W(TBD)
Size	: 194mm x 34mm x 42mm (without bracket)
Net Weight	: 0.5Kg(TBD)
MTBF	: 30000h

Ordering Information

Part code : PPU-IVC-4K-120AF

GLOBAL HEADQUARTERS

Q3-A3, 10th Floor, Cyber Towers, Hitech City,
Madhapur, Hyderabad - 500 081 (India)
Phone: +91 (40) 66903959 / 60
Email: vc@peoplelinkvc.com

INTERNATIONAL CONTACT NUMBERS

USA : +1-321-2163070
UK : +44-20-35190197

Africa : +27-10-5001977
Australia: +61-29-0988367

Canada : +1-647-4964195
Middle East : +973-1-6199342

Follow us:       www.peoplelinkvc.com/social-presence

DISCLAIMER: PeopleLink Unified Communications Pvt. Ltd., All rights reserved. All third party trademarks / products mentioned (if any) are the property of their respective owners. Product Images are for illustration purpose only. Actual product may vary due to product enhancements. All specifications are subject to change without notice; system specifics may vary.

PeopleLink Public Document | PeopleLink Unified Communications Pvt. Ltd. | ISO 9001:2015 & ISO/IEC 27001:2013 Certified Company.