

[CLICK TO WATCH VIDEO](#)



## PVC 50WS

PeopleLink PVC 50WS is a digital wireless Speakerphone that is the perfect audio solution for boardrooms and conference rooms. The microphones has 360 degree audio pickup capability and delivers upto 87db of clear audio output. The echo cancellation and noise reduction features help in preventing background noise and echoes from interfering with the conference.



**Speaker phone:** Simultaneously uses a microphone and loudspeaker without the need for a headset/handheld unit



**Wireless unit:** Permits meetings to be managed with complete control and reliability



**Omni directional microphone:** These microphones can pick up sound equally from all directions



**87db speaker out:** Produces high fidelity audio quality



**Built in AEC, AGC and ANS:** Acoustic Echo Cancellation, Automatic Gain Control, and Acoustic Noise Suppression



[CLICK TO VISIT WEBPAGE](#)

# Applications

- Area of Application: Board room & Conference room
- Ideal Room size: 20ft by 15ft
- Capacity: 8 to 10 seater
- Shape of the table: Recommended for oval shape



[CLICK TO VISIT WEBPAGE](#)

# Specifications

## PVC 50WS

### I/O

Interface	USB 2.0, 3.5mm out
Frequency Range	2.400 GHz~2.4835 GHz.

### PHONE SET FEATURES

Keypad Flash	Microphone zone selection, Volume Up/Down, Microphone Mute, Speaker Mute
--------------	--

### USER INTERFACE

USB Nos.	1 Nos	Mute Indicators and Number	Yes
USB type	USB 2.0 B Type		

### AUDIO TECHNOLOGY

DSP based Echo cancellaion	Yes
----------------------------	-----

### AUDIO FEATURES

Speaker Gain Control	< 12dB	Noise reduction	< 16dB
Automatic Level Control	< 18dB	Speaker output	87dBA
		Power Consumption	2.5W
		Frequency Range	2.400 GHz~2.4835 GHz.

Built-in Microphones 1 Nos  
Microphone pickup range up to 10 ft.  
Audio Input 1 x USB 2.0

Audio Output 1 x 3.5mm Stereo Line-Out  
Background Noise Supression < 16dB

## ENHANCED AUDIO FEATURES

Automatic Echo Cancellation	Yes	Non Linear Processing	Yes
Automatic Gain Control	Yes	Automatic Level Control	Yes
Noise Reduction	Yes		
Full Duplex	Yes		

## RECOMMENDED ROOM CONDITIONS

Reverberation time	<0.5 second	Noise Level	<48 dBA
--------------------	-------------	-------------	---------

## ELECTRICAL

Power Operating Temperature	USB bus powered (DC 5V/500mA) 0°C to 40°C	Environmental Humidity	20-85% (RH)
-----------------------------	--	------------------------	-------------

## PHYSICAL CHARACTERISTICS

Package Dimension	155 mm x 148 mm x 37 mm (L x W x H) 270 mm x 230 mm x 83 mm (LxWxH)	Net Weight Gross Weight	312 grams 660 grams (Package)
-------------------	--	----------------------------	----------------------------------

## PACKING INFORMATION

Contains USB Cable (1.8 mtr.), User Manual.Wireless Dongle

## ORDERING INFORMATION

PeopleLink PVC 50 PPU-PVC-AD-50WS

## APPLICATION

Room type	Board room Or conference room	Capacity	8 to 10 seater
Room size	20Ft X 15Ft	Table shape	Recommended for Oval shape table

### GLOBAL HEADQUARTERS

Q3-A3, 10th Floor, Cyber Towers, Hitech City,  
Madhapur, Hyderabad - 500 081 (India)  
Phone: +91 (40) 66903959 / 60  
Email: vc@peoplelinkvc.com

### INTERNATIONAL CONTACT NUMBERS

USA : +1-321-2163070	Africa : +27-10-5001977	Canada : +1-647-4964195
UK : +44-20-35190197	Australia: +61-29-0988367	Middle East : +973-1-6199342

Follow us:       [www.peoplelinkvc.com/social-presence](http://www.peoplelinkvc.com/social-presence)

DISCLAIMER: PeopleLink Unified Communications Pvt. Ltd., All rights reserved. All third party trademarks / products mentioned (if any) are the property of their respective owners. Product Images are for illustration purpose only. Actual product may vary due to product enhancements. All specifications are subject to change without notice; system specifics may vary.

PeopleLink Public Document | PeopleLink Unified Communications Pvt. Ltd. | ISO 9001:2015 & ISO/IEC 27001:2013 Certified Company.