



 [CLICK TO WATCH VIDEO](#)

Integrated 4K Huddle Endpoint

PeopleLink InstaVC 4K endpoint delivers high definition experience of video conference at an optimized bandwidth. The integrated compact design houses powerful 4K camera, microphone & processor to host 16 member multiparty video conference. Connect two displays to view content as well as people on two different screens. The webRTC technology enables the invited members to join the call directly from web browser on any device without downloading a software.



8X Digital Zoom



4K Ultra High Definition Videoconference



allow members to join the call directly from web browser



Built-in microphone



Distribute incoming videos across two screens



Collaboration tools such as document & screen sharing, white board, & annotation



 [CLICK TO VISIT WEBPAGE](#)

Applications

- Area of Application: Board room & Conference room

Specifications

Integrated 4K Huddle Endpoint



[CLICK TO VISIT WEBPAGE](#)

SYSTEM UNITS

Include Packages

HD codec (built-in HD camera) x 1
Remote control x 1 AC power adapter x 1 AC power cable x 1 HDMI cable (1.5m) x 2
User manual (Quick Start, Quick Installation Guide) x 1

HARDWARE PLATFORM

Operating system

Android 6.0

Processor (CPU)

(MTK) Helio X20 series chips based on 64-bit 10 cores: 2 Cortex-A72 2.3GHz, 4 Cortex-A53 2.0GHz Cortex-A53 + 4 1.5GHz Cortex-A53 processors

Image Processor (GPU)

Built-in MALI T880-MP4 850MHz graphics processor

Memory

Built-in 16G Bytes Flash, 3G Bytes LPDDR3, 800MHz memory, maximum optional 32G T-Flash card

Video codec

HEVC decoder 2160p@30fps VP9 decoder 2160p@30fps
H.264 decoder: 2160p@30fps
Sorenson H.263/H.263 , decoder:1080p@60fps/40Mbps MPEG-4 SP/ASP decoder:1080p@60fps/40Mbps
DIVX4/DIVX5/DIVX6/DIVX HD/XVID , decoder: 1080p@60fps/40Mbps
MPEG-4 encoder: Simple profile D1@30fps
263. encoder: Simple profile D1@30fps
264.encoder: High profile 2160p@30fps HEVC encoder: Main profile 2160p@30fp

Audio codec	Audio content sampling rates supported: 8kHz to 192kHz Audio encoding: AMR-NB, AMR-WB, AAC, OGG, ADPCM Audio decoding: WAV, MP3, MP2,AAC, AMR-NB, AMR-WB, MIDI, Vorbis, APE, AAC-plus v1, AAC-plus v2, FLAC,WMA, ADPCM
Wirelesschip	(MTK) MT6631, Wifi+BT+GPS triple chip, MT6176 RF transceiver chip

VIDEO SPECIFICATIONS AND FEATURES

Digital Zoom	8X
People Video Resolution	1080p, bandwidth: 512Kbps 720p, bandwidth: 384Kbps 4SIF/4CIF, bandwidth: 128Kbps SIF/CIF/QSIF/QCIF/SQSIF/SQCIF,bandwidth: 64KbpsA
Content Video Resolution	Input: Built in 4K camera or Miracast Coding/Decoding Resolution: 800x600, 1024x768, 1280x1024, 1280x720, 1920x1080 Output: 800x600, 1024x768, 1280x1024, 1280x720, 1920x1080
Dual Stream	Dual 1080p or dual 720p
Built-in 1080p HD Camera	input: 4K(3840x2160)@30fps/25fps; Sensor: 800x600, 1024x768, 1280x1024, 1280x720, 1920x1080 Scan mode: 800x600, 1024x768, 1280x1024, 1280x720, 1920x1080 Focal length: f= 3.5mm FOV:84° (Optional 120°) Auto focus: Support
Other VideoFeatures	PIP (Picture in Picture), PoP (Picture outside Picture)

AUDIO SPECIFICATIONS AND FEATURES

Audiofeatures	AEC (Acoustic Echo Cancellation) AGC (Automatic Gain Control) ANS (Acoustic Noise Suppression) Lip synchronization
---------------	---

INTERFACE

Audio input interface	1 x built-in microphone input
Audio output interface	1 x 3.5mm linear output
Video input interface	1 x Built-in fixed-focus 4K camera input (supports ePTZ function)
Video output interface	2 x HDMI
USB interface	1 x USB2.0
TFinterface	1 x TF card interface
NetworkInterface	1 x RJ45: 10/100 Base-T

PHYSICAL CHARACTERISTICS

Dimensions

Codec dimensions (L x W x H): 195mm x 34mm x 59mm
Package dimensions (L x W x H): TBD
Net weight: TBD Package weight: 0.25Kg

Working voltage: DC 12V Power consumption: 12W

Electrical

Environmental Specification

Operating temperature: 0°C to 40°C Operating humidity: 10% to 80%
Non-Operating temperature: -40° to -70°C
Non-Operating humidity (non-condensing): 0% to 95%
Peripheral noise: < 46 dBA SPL
Lowest luminance: 5 lux Recommended luminance: > 300 lux

Ordering Information

Part code : PEP-INT-HUD-4K

GLOBAL HEADQUARTERS

Q3-A3, 10th Floor, Cyber Towers, Hitech City,
Madhapur, Hyderabad - 500 081 (India)
Phone: +91 (40) 66903959 / 60
Email: vc@peoplelinkvc.com

INTERNATIONAL CONTACT NUMBERS

USA: +1-321-2163070
UK: +44-20-35190197

Africa: +27-10-5001977
Australia: +61-29-0988367

Canada: +1-647-4964195
Middle East: +973-1-6199342

Follow us:       www.peoplelinkvc.com/social-presence

DISCLAIMER: PeopleLink Unified Communications Pvt. Ltd., All rights reserved. All third party trademarks / products mentioned (if any) are the property of their respective owners. Product Images are for illustration purpose only. Actual product may vary due to product enhancements. All specifications are subject to change without notice; system specifics may vary.

PeopleLink Public Document | PeopleLink Unified Communications Pvt. Ltd. | ISO 9001:2015 & ISO/IEC 27001:2013 Certified Company.