



PeopleLink DSP-CM

Experience High quality audio communication with PeopleLink's voice collaboration DSP, convert your Classrooms, Training Rooms, Boardrooms with the ease of technology for conferencing.

DSP-CM is integrated with high signal-to-noise ratio, adaptive echo cancellation, adaptive noise suppression and function of intelligent sound mixing. Ceiling microphone is designed to cover meeting spaces, such as training rooms, classrooms, demo rooms, with discreet and easy ceiling mounting.



Recommended for
PeopleLink powered Video Collaboration
Solutions

Key Features

- HD voice pickup range mic
- The 3rd Generation of Auctopus Audio Processing Algorithm
- Efficient Layout
- Compatible with common audio and video software

Specifications

| | |
|-----------|---|
| Component | : Digital audio processor |
| | : DSP processing bus structure |
| | : B-type USB connection |
| | : 2 road 3.81mm phoenix interface |
| | : input and output single adjustment knob |
| | : suspended spherical microphone |
| Interface | : B-type USB interface |
| | : DC 12V power interface |
| | : 2 road 3.81mm phoenix interface |

Power Supply

| | |
|--------------|-----------------------------------|
| Power Supply | : power adapter |
| | : input: 100-240v, 0.5A, 50/60Hz. |
| | : output: DC 12V,2A |

Audio Features

| | |
|-----------------|--|
| Audio processor | : frequency response (20hz-20khz @+4dBu) |
| | : microphone channel: +0/ -2db. |
| | : line input channel: +0/-0.5dB. |
| | : Light |
| | : Work normal , red, green alternatively lighting on Certification |
| Audio features | : adaptive echo cancellation. |
| | : adaptive noise suppression. |
| | : intelligent remix |

Support

Windows 7 / Windows 10 /Windows XP, Mac OS

Temperature

Temperature : Temperature:20°~70°
: humidity:20~90% condensation free
: noise level:<48dB
: storage temperature:20°~70°

Microphone

Microphone : Pick up radius: 10m Max
: Frequency response: 50hz-20khz
: Sensitivity :-47 plus or minus 3dB.
: SNR: 75dB

Ordering Information

Part codes

Peoplelink **DSP-CM** : PCU-DSP-CM

GLOBAL HEADQUARTERS

Q3-A3, 10th Floor, Cyber Towers, Hitech City,
Madhapur, Hyderabad - 500 081 (India)
Phone: +91 (40) 66903959 / 60
Email: vc@peoplelinkvc.com

INTERNATIONAL CONTACT NUMBERS

USA : +1-321-2163070
UK : +44-20-35190197

Africa : +27-10-5001977
Australia: +61-29-0988367

Canada : +1-647-4964195
Middle East : +973-1-6199342

Follow us:       www.peoplelinkvc.com/social-presence

DISCLAIMER: PeopleLink Unified Communications Pvt. Ltd., All rights reserved. All third party trademarks/ products mentioned (if any) are the property of their respective owners. Product images are for illustration purpose only. Actual product may vary due to product enhancements. All specifications are subject to change without notice; system specifics may vary.

PeopleLink Public Document | PeopleLink Unified Communications Pvt. Ltd. | ISO 9001:2015 & ISO/IEC 27001:2013 Certified Company.