



[CLICK TO WATCH VIDEO](#)

QUADRO

PeopleLink Quadro is a Hybrid Conference phone. The 360 degree pan audio pickup feature allows to capture audio from every corner of the room. The device delivers 92db audio output which is completely free from any background noise interference or echoes.



USB Speakerphone :
An Ideal audio conferencing solution



Digital Conference Units :
Permits meetings to be managed with complete control and reliability



4 bi-directional microphones (360 degrees):
These microphones can pick up sound equally from all directions



92 dB Speaker Out:
Produces high fidelity audio quality



Built in AEC, AGC & ANS :
Acoustic Echo Cancellation, Automatic Gain Control, and Acoustic Noise Suppression



Built-in Digital Signal Processing (DSP) technology



[CLICK TO VISIT WEBPAGE](#)

Applications

- Area of application: Board room or conference room
- Ideal Room size: 30ft by 20ft
- Capacity: 15 to 20 seater
- Shape of table: Recommended for oval shape table



 [CLICK TO VISIT WEBPAGE](#)

Specifications

QUADRO

I/O

Interface	: USB, Ext1, Ext 2, Power jack	Frequency Range	: 100 Hz to 22KHz
-----------	--------------------------------	-----------------	-------------------

USER INTERFACE

Screen Size	: 58x28mm, 4 Lines	Mute Indicators and Number Buttons	Mute Indicator and Numbers
USB Nos.	: 1 Nos		Lync Off hook Key, Lync Hang Up,
USB type	: USB 2.0 B TypeB		Mute Mic, Mute Speaker, Vol Up/Down

AUDIO TECHNOLOGY

DSP based Echo cancellaion	: (Echo Tail) 500ms.0
----------------------------	-----------------------

AUDIO FEATURES

Speaker Gain Control	: Max:92dB	Frequency Range	: 100 Hz to 22KHz
Noise reduction	: 18dB	Built-in Microphones	: 4 Nos
Speaker output	: 92dBA	Microphone pickup range	: Upto 3 mtr, 5 mtr with Extension
Power Consumption	: <6W	Audio Input	: 1x USB 2.0 B Type

ENHANCED AUDIO FEATURES

Automatic Echo Cancellation	Yes	Non Linear Processing	Yes
Automatic Gain Control	Yes	Automatic Level Control	Yes
Noise Reduction	Yes		
Full Duplex	Yes		

ELECTRICAL

Power	100-240V ~50/60Hz 0.4A	Storage Temperature	0°C-50°C
Operating Temperature	0°C - 50°C	Environmental Humidity	0-85%

PHYSICAL CHARACTERISTICS

Dimension	LxWxH:350x350x55mm	Gross Weight	2.10kg
Net Weight	1.25kg		

PACKING INFORMATION

Contains	User Manual , Power adaptor, 6.5 Meter Power Extension Cable	Optional Accessories	4P4C Cable x 3 Pcs, Extension Microphone (upto 2 Pcs),
----------	--	----------------------	---

ORDERING INFORMATION

PeopleLink Quadro **PeopleLink Quadro** : PPU-PVC-CP-QOD
PeopleLink Quadro Ext :PPU-PVC-CP-QOD-E (with Extension Microphones)

GLOBAL HEADQUARTERS

Q3-A3, 10th Floor, Cyber Towers, Hitech City,
Madhapur, Hyderabad - 500 081 (India)
Phone: +91 (40) 66903959 / 60
Email: vc@peoplelinkvc.com

INTERNATIONAL CONTACT NUMBERS

USA : +1-321-2163070 Africa : +27-10-5001977 Canada : +1-647-4964195
UK : +44-20-35190197 Australia: +61-29-0988367 Middle East : +973-1-6199342

Follow us:

www.peoplelinkvc.com/social-presence

DISCLAIMER: PeopleLink Unified Communications Pvt. Ltd., All rights reserved. All third party trademarks / products mentioned (If any) are the property of their respective owners. Product Images are for illustration purpose only. Actual product may vary due to product enhancements. All specifications are subject to change without notice; system specifics may vary.

PeopleLink Public Document | PeopleLink Unified Communications Pvt. Ltd. | ISO 9001:2015 & ISO/IEC 27001:2013 Certified Company.

www.peoplelinkvc.com

