

Intelligent Conference terminal :

Equipped with multi-touch and FHD screen, **Quadro Touch** conference phone supports Ethernet/WIFI/ Bluetooth connection and USB port for Camera input, HDMI port for Video output. It is suitable for large and medium conference rooms.

High quality Audio Experience :

Quadro Touch has fast processing power, strong anti-jamming capability and strong echo cancellation and noise cancellation algorithm with built in DSP and ARM Dual-Core processor. Its voice pickup range can be up to 5 meters.

Modular Camera input and Display output

It supports camera with USB 2.0 interface and projection with HDMI 2.0 interface.

Team Collaboration at Multiple interfaces

Quadro Touch supports multiple conference interfaces , such as SIP, USB and Bluetooth which makes team collaboration more convenient and reduces cost drastically.



PeopleLink Quadro Touch

Product Features

> High-definition screen

5.5-inch FHD screen

- dual-core processor and large storage
 Built-in high efficient DSP, ARM Dual-Core processor makes
 system processing speed more faster
- Quadro Touch audio High-tech
 360-degree mic coverage 256ms acoustic echo cancellation
 Full duplex Dynamic Noise Reduction (DNR)
- IP teleconference
 SIP meeting by Ethernet/WIFI/ connection
- > Online meeting

Supports audio of IM software based on computer USB /Bluetooth connection, such as PeopleLink InstaVc.

Three-party conference

Users can call the third party without interrupting the call

> Variety hardware interface

Supporting USB 2.0 Camera, mouse and HDMI2.O projection

- Smart UI
 Date synchronization based on SNTP and customize setting
- > Extend Mic and loudspeaker

Product Specifications

Module

- Multi-touch screen
- 5.5 inch FHD screen (1080×1920 pixel)
- Vertical screen keyboard
- One USB 2.0 Type A interface
- One HDMI 2.0 interface
- Bluetooth 4.0 wireless connection
- LED indicator

Audio features

- 360-degree mic coverage (up to 80 square meter voice pick up distance)
- 256ms acoustic echo cancellation
- Full duplex
- Dynamic Noise Reduction(DNR)
- DSP,ARM dual-core processor





Product Specifications

Size

- 407*354*78 mm
- 466*404*104 mm(package)

Net weight

• 950g

Color

• Black

Microphone

- Omnidirectional digital microphone
- Frequency response: 100Hz-8000Hz
- Sound pressure: 94dB SPL@1kHz
- Distortion rate: 5%@100dB SPL
- Sensitivity:
- 22dB@1kHz(0dB=1V/Pa)

Loudspeaker

- Power: 4 Ω 10W
- Frequency response: 100Hz~ 22000Hz
- Maximum output: 92dB @0.5 m
- Distortion rate:
- 5% MAX @1000Hz 3W

Power

• 12V/2000mA

System configuration

- Android 5.1
- ARM 4 core CPU up to 1.8GHz main frequency
- 2G RAM, 16G ROM

Network

- WIFI
- 802.11a/b/g/n
- Ethernet
- 10M/100M/1000M Base-TX

Operation system

• Windows® 7,8.1,10/ Mac OSX10.7 or higher operation system

Function

- IP conference
- IM software conference Such as InstaVc
- Real time Bluetooth audio
- HDMI projection
- External USB camera/mouse
- Indicator
- Incoming display
- Incoming record
- Address book
- Microphone mute
- Volume up/down
- Language selection
- Customized setting

Interface

- B type USB
- 10M/100M/1000M Ethernet (RJ45)
- Power
- HDMI2.0
- USB 2.0

Touch key

- Microphone mute
- Volume up/ down

LED indicator

- Green: working status
- Red: microphone mute

Certification

• CCC, CE



Product execution standard

- YD/T 993-1998
- GB/T 9254-2008
- GB 4843.1-2011

Recommended conditions

- Temperature: 5°~44°
- Humidity: 20~85% condensation free
- Storage temperature: -10°~55°

Warranty

• 1 year warrenty

Ordering Information

Quadro Touch

Part code

: PPU-PVC-CP-QODT

GLOBAL HEADQUARTERS

Q3-A3, 10th Floor, Cyber Towers, Hitech City, Madhapur, Hyderabad - 500 081 (India) Phone: +91 (40) 66903959 / 60 Email: vc@peoplelinkvc.com

INTERNATIONAL CONTACT NUMBERS

USA:+1-321-2163070 UK:+44-20-35190197 Africa : +27-10-5001977 Australia: +61-29-0988367 Canada : +1-647-4964195 Middle East : +973-1-6199342

Follow us: $(\mathbf{in}) (\mathbf{y}) (\mathbf{f}) (\mathbf{p}) (\mathbf{G}) (\mathbf{g})$ www.peoplelinkvc.com/social-presence

DISCLAIMER: PeopleLink Unified Communications Pvt. Ltd., All rights reserved. All third party trademarks / products mentioned (If any) are the property of their respective owners. Product Images are for illustration purpose only. Actual product may vary due to product enhancements. All specifications are subject to change without notice; system specifics may vary.

PeopleLink Public Document | PeopleLink Unified Communications Pvt. Ltd. | ISO 9001:2015 & ISO/IEC 27001:2013 Certified Company.

