



PeopleLink Speaker Track Pro

PeopleLink Speaker Track camera helps to achieve intelligent meeting experience, implemented with both audio positioning and intelligent video analysis technologies. It can automatically switch between close-up image and full-view image to frame the speaker(s). It frees of camera operation during a meeting and enables meeting attendees to focus more on discussion.

Key Features

- 1/2.8" CMOS, 2.14MP
- 12x optical zoom, up to 72.5° FOV
- Simultaneously output 3G-SDI, HDMI, Ethernet, up to 1080P60 resolution
- Support H.264/H.265 video compression
- Implemented with both audio positioning, body detection and recognition technologies, it can precisely frame the speakers
- Automatically switch between close-up image for speaker(s) and wide-angle image for all attendees
- Built-in image switch rules according to actual meeting scenarios.

Specifications

FEATURES

Image Sensor	: 1/2.8"CMOS, 2.14MP
Signal Format(SDI)	: 1080P60, 1080P50, 1080P30, 1080P25, 1080I60, 1080I50, 720P60, 720P50
Focal	: f=3.9mm-46.8mm
Iris	: F1.6-F2.8
Optical Zoom	: 12x
Digital Zoom	: 12x
Field of View	: 72.5°-6.3°
Focus	: Auto, Manual, PTZ Push, One Push
Min. Illumination	: 0.5Lux (Colour), 0.1Lux (B/W)
Shutter Speed	: 1/25-1/10,000s
AGC	: Auto/Manual
White Balance	: Auto, Indoor, Outdoor, One Push Manual, Auto Track
AE Control	: Auto, Manual, Shutter Priority, Iris Priority
S/N	: ≥50dB
DNR	: 2D/3D
BLC	: Support

Camera

Pan Range	: 90°~+90°
Tilt Range	: -30°~+90°
Pan Speed	: 0.1°~120°/ s
Tilt Speed	: 0.1°~80°/s
Preset Number	: 256
OSD	: Yes
Image Flip	: Yes

Network

Max. Image Size	: 1920×1080 @60 fps
Video Compression	: H.265,H.264
Audio Compression	: AAC
Protocol	: HTTP,RTSP,RTMP,RTP,TCP,UDP,ONVIF
Dual Stream	: Support

Interface

Video Output	: 1×HDMI Interface,1×3G-SDI Interface,
Audio Input	: 2×LINE IN, including one channel with EC
Audio Output	: 1×LINE OUT
Network Interface	: 1×10M/100M
USB Interface	: 1×USB2.0
Control Interface	: 1×RS-232

General

Control Protocol	: VISCA, PELCO-P, PELCO-D
Address	: 0~63
Power Supply	: DC12V
Power Consumption	: <50W
Working Temp	: 0°C ~ + 40°C
Storage Temp	: -20°C ~ +60°C
Dimension (L×W×H)	: 500 mm x 162mm x 137mm
Weight	: 3kg

Ordering Information

Part code

Speaker Track Pro : **PEP-PIS-STP**

GLOBAL HEADQUARTERS

Q3-A3, 10th Floor, Cyber Towers, Hitech City,
Madhapur, Hyderabad - 500 081 (India)
Phone: +91 (40) 66903959 / 60
Email: vc@peoplelinkvc.com

INTERNATIONAL CONTACT NUMBERS

USA : +1-321-2163070
UK : +44-20-35190197

Africa : +27-10-5001977
Australia: +61-29-0988367

Canada : +1-647-4964195
Middle East : +973-1-6199342

Follow us:       www.peoplelinkvc.com/social-presence

DISCLAIMER: PeopleLink Unified Communications Pvt. Ltd., All rights reserved. All third party trademarks/ products mentioned (if any) are the property of their respective owners. Product Images are for illustration purpose only. Actual product may vary due to product enhancements. All specifications are subject to change without notice; system specifics may vary.

PeopleLink Public Document | PeopleLink Unified Communications Pvt. Ltd. | ISO 9001:2015 & ISO/IEC 27001:2013 Certified Company.