



e-Podium Elite

PeopleLink ePodium Elite delivers unmatched Interactivity among various digital devices with its ergonomic design which allows you to collaborate with your partners, Customers and business associates with technological ease; it provides great productivity benefits due to its modular form factor, achieving easy mobility of the device

Area Of Applications

Area of application:

Classroom/Training room/Auditorium

Capacity: 60 to 80 seater



Specifications

e-Podium ElitePlus

BODY MATERIAL

Body	: Metallic
Top	: Metallic
Top Sliding Mechanism	: Yes
Provision for Monitor	: Yes (upto 22 inches)
Electronic Monitor Lift	: Yes
Document Camera Tray	: Yes (Sliding Type)
RFID	: Optional

TABLET MONITOR FEATURES

Screen Size	: 21.5" wide LED
Resolution	: 1920 x 1080
PC Connection	: USB Port
Luminosity	: 250 cd/m2
Input	: DVI, HDMI
Number of Colours	: 16.7M
Response time	: 5ms
Contrase ratio	: 1000/1
Operating System	: Windows, Linux, Mac.

ELECTRICAL

Input Voltage	: DC 12V
Power : 100 – 250V AC	: 100 – 250V AC.

Digital Signal Processor

Frequency Range	: 30Hz -15000 Hz
Automatic Echo Cancellation	: Yes
Automatic Gain Control	: Yes
Dynamic Noise Reduction	: Yes
Full Duplex	: Yes
Line Input	: 1x Line Input
Line Output	: 1 x Line Output
USB Audio Port	: 1 x USB Port

Multi Channel Digital Signal

Package Includes

Microphone Options	: 1 lapel + 2 Handheld
Frequencies Response	: 50 Hz-18000 Hz
Antennas	: 2 x 3dBi
Output	: Balanced Out x2, Mixed Out x 1
Volume Control	: Yes
Amplifier	: Yes
Line Input	: 1x Balanced, 1 x Unbalanced.
Phantom	: Yes (15 V for Balanced Input)
Power output @8 ohms	: 50 Watts x2
Minimum impedance	: 8 Ohm
Frequency response	: 20Hz-20000Hz
Speakers (1Pair)	: 50 Watts Speaker (1" Titanium Dome Tweeter, 5.25" Polypropylene Woofer, 90-20KHz Frequency response),

Central Controller

Ethernet	10/100 Mbps, Full / Half Duplex, IPV4
RS-232 Port	Total 4 dedicated RS-232C Ports. (3-pin 3.81 mm detachable terminal; Bidirectional TTL/RS-232 (0-5 Volts) port with up to 115200 baud rate).
RS-232/IR Hybrid Port	Total 3 RS-232C/IR Ports (3-pin 3.81 mm detachable terminal; Comprises IR/Serial out put ports; Bidirectional TTL/RS-232 (0-5 Volts) port with up to 115200 baudrate when configured as serial; One-way IR output when configured as IR Emitter.
Relay Switch Port	Total 10 blocks (each 2-pin 3.81 mm detachable terminal; Comprises normally open, Non-Isolated relays; Rated 6 Amp, 230 Volts AC or 110 Volts DC max.
Power	One 3.5 mm DC power jack connector associated with a Power Switch on rear panel; 12 Volt DC power input and 1.5 Amp max current rating
Operating Temperature	50° to 113° F (10° to 45° C)
Humidity:	RH Non-Condensing 15% to 85%. Heat Dissipation: 45 BTU/hr.
Analog Signal	One 3.5 mm DC power jack connector associated with a Power Switch on rear panel: 12 Volt DC power input and 1.5 Amp max current rating.

Gooseneck Microphone Features: (Optional)

Cartridge	: 20mm Condenser
Frequency Response	: 40~20000 Hz.
Polar Pattern	: Cardioids
Connectors	: 3-Pin XLR

Control Pad

Control Pad	: 7 Inches Touch Screen
Resolution :	: 800 x 480
Interface :	: WiFi.
Power	: 12V / 1A
Size	: 7 Inches
Type	: Touch Screen
Internal Memory	: 2 GB

Laptop Interface

Laptop Interface	: Inbuilt
Video Port For laptop	: 1x VGA, 1x HDMI
Audio Port For Laptop	: 1x 3.5mm Stereo Female Port
LAN Port	: 1x RJ-45
USB 2.0 Ports	: 4x USB 2.0 Ports, 1xUSB (Laptop Touch & DSP), 1xUSB (CPU Touch & DSP)
Power Socket	: 3 Pin AC 220 Power Socket
RS-232 Port	: Yes
Video Ports	: 4 Ports, 2 x Laptop, 1 x PC, 1 x Visualiser
Switcher	: Inbuilt

CPU (Optional)

Processor	: Intel i3 / i5
RAM	: 4 GB
HDD	: 1000 GB
Operating System	: Windows 10
Keyboard/Mouse	: Yes

CONTENTS

Components

Accessories

1.5 Mtrs HDMI Cable x4, 3.5mm Male to Male x 2, Stereo to 2 RCA x 2, USB 2.0 M to M x4.

Part code

: **PCU-PDP-EP-ELITE**

GLOBAL HEADQUARTERS

Q3-A3, 10th Floor, Cyber Towers, Hitech City,
Madhapur, Hyderabad - 500 081 (India)
Phone: +91 (40) 66903959 / 60
Email: vc@peoplelinkvc.com

INTERNATIONAL CONTACT NUMBERS

USA : +1-321-2163070
UK : +44-20-35190197

Africa : +27-10-5001977
Australia: +61-29-0988367

Canada : +1-647-4964195
Middle East : +973-1-6199342

Follow us:       www.peoplelinkvc.com/social-presence

DISCLAIMER: PeopleLink Unified Communications Pvt. Ltd., All rights reserved. All third party trademarks/ products mentioned (if any) are the property of their respective owners. Product Images are for illustration purpose only. Actual product may vary due to product enhancements. All specifications are subject to change without notice; system specifics may vary.

PeopleLink Public Document | PeopleLink Unified Communications Pvt. Ltd. | ISO 9001:2015 & ISO/IEC 27001:2013 Certified Company.