



PeopleLink Impact Digital Microphone



PeopleLink Impact Digital microphone is a plug & play digital microphone which can cascade up to 4 (Total) it is ideal for Huddle room to Large Conference rooms. They are an accessory of the Impact Series Endpoints.

PRODUCT FEATURES

Omnidirectional, full function.

With 360° pickup range, star microphone array, wide-range frequency response, support analog output.

Intelligent voice tracking

Auto Focus on the current speaker without human intervention, clear voice and low noise.

Large pickup area

Pickup covers an area of 60 square meters, three times bigger than similar products.

Beautiful and high efficient

Electronic devices can be pleased on the desktop, more simple, beautiful and efficient.

Perfect voice quality

Desktop mount, optimize the audio acquisition, real voice to show.





PeopleLink Impact Digital Microphone

Technical Specifications:

Basic:

Transducer Principle: Back Electret Condenser

Directivity Characteristic: 360°

Pickup Radius: 6m

Frequency Response: 40Hz ~ 20KHz

Sensitivity: $-38dB \pm 2dB$ (0dB = 1V / Pa at 1KHz)

Output Impedance : $500\Omega \pm 30\%$ (at 1kHz) Equivalent Noise Level : <50dBA SPL

Max. Input SPL: 103dBA SPL

Max Cascade Number on Single Group: 4

AEC: Support **AGC**: Support **ANS**: Support

Mute button: Support General Specifications:

Input Voltage: 12V ~ 48V (PoE)

Current Consumption: 0.1A

Operating Temperature : $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Storage Temperature : $-20^{\circ}\text{C} \sim +60^{\circ}\text{C}$

Power Consumption: 4.8W

Dimensions: 160mm x 35mm

Net Weight: 291g

Input/Output Interface:

System Lamp

• Red light : Mute

• Blue light: Not Mute

NOTE:

 When the mute button is touched, Microphone will only send key info to main control device, and the indicator state will change according to the instruction to the instructions of the main control device.

Uplink

Digital Port -1

 RJ45: Embedded power supply and analog audio input and output, with audio input (echo reference) light

Downlink

Digital Port -2

 RJ45: Power supply and digital audio input and output, with link light

Ordering Information:

PeopleLink Impact Digital Microphone : **PEP-PIS-ACC-MIC-D**

LEARN MORE

For more information on PeopleLink Impact Digital Microphone Click Here

SALES AND INQUIRIES -

Global Headquarters

Q3-A3, 10th Floor Cyber Towers, HITEC City, Hyderabad, Telangana 500081, **India Phone:** +91 9100123013 **Email:** vc@peoplelinkvc.com

International Contact Numbers

USA: +1 669-696-8383 Australia: +61 370 037070 France: +33 6 80 75 26 42 Middle East: +966 5300 19292 UK: +44 20 4571 5454

UAE: +971 4 3339082 Canada: +1 647-945-7373 Malaysia: +(6)018-2872188 New Zealand: +64-9-802-4666 Africa: +254 107 529 656

Tech Support

Toll Free: 1800 208 3399 customersupport@peoplelinkvc.com