



PeopleLink PVC 50WS Cascade





PeopleLink PVC 50WS Cascade is a portable, digital wireless conference microphone for conference and board rooms. It can be easily connected to a laptop or PC through USB ports. Features like echo cancellation and noise reduction suppress unwanted background noise and echo for crystal-clear audio during video conferencing.

Key Features

- Digital wireless cascade conference units: Permits meetings to be managed with complete control and reliability.
- Omni directional microphone:
 These microphones can pick up sound equally from all directions.
- Built in AEC, AGC and ANS: Acoustic Echo Cancellation, Automatic Gain Control, and Acoustic Noise Suppression
- **OTA:** Up to 5 Mbps over-the-air (OTA) data rate





General Specifications

I/O

Interface: USB 2.0 (full), 3.5mm out

Frequency Range : 2.400 GHz ~ 2.4835 GHz.

OTA: 5 or 2 Mbps Over-the-Air Data Rate

Phone Set Features

Keypad Flash: Microphone zone selection, Microphone

Mute

User Interface

USB Nos.: 1

Frequency Range: USB 2.0 B Type
Mute Indicators and Number: Yes

Audio Technology

DSP-based Echo Cancellation: Yes

Audio Features

Automatic Level Control: < 18dB

Noise Reduction : < 16dB Power Consumption : 2.5W

Frequency Range: 2,400 ~ 2,483 GHz

Audio Input: 2.5W

Enhanced Audio Features

Automatic Echo Cancellation : Yes

Automatic Gain Control: Yes

Noise Reduction : Yes

Full Duplex: Yes

Non Linear Processing: Yes
Automatic Level Control: Yes

Recommended Room Conditions

Reverberation Time: < 0.5 seconds

Noise Level: <48 dBA

Electrical

Power Operating: USB bus powered (DC

5V/500mA)

Temperature: 0°C to 40°C

Environmental Humidity: 20-85% (RH)

Packing Information

USB Cable, Host and antenna, Wireless Mics, Power

adapters, Audio cables, User manual

Application


Room type: Board room or conference room

Room size: 40ft x 30ft


Capacity Table Shape : 10 to 24 seater (Recommended for Oval or U shape table)




Application Scenarios







Disclaimer:- Room setup diagrams provided for reference only. Actual room setup and size may vary as per requirements.



Ordering Information

PeopleLink PVC 50WS 2 Cascade

PeopleLink PVC 50WS 3 Cascade

: PPU-PVC-AD-50WS-2C

: PPU-PVC-AD-50WS-3C

LEARN MORE

For more information on PVC 50WS Cascade Click Here

SALES AND INQUIRIES -

Global Headquarters

Q3-A3, 10th Floor Cyber Towers, HITEC City, Hyderabad, Telangana 500081, **India Phone:** +91 9100123013 **Email:** vc@peoplelinkvc.com

International Contact Numbers

USA: +1 669-696-8383 Australia: +61 370 037070 France: +33 6 80 75 26 42 Middle East: +966 5300 19292 UK: +44 20 4571 5454

UAE: +971 4 3339082 Canada: +1 647-945-7373 Malaysia: +(6)018-2872188 New Zealand: +64-9-802-4666 Africa: +254 107 529 656

Tech Support

Toll Free: 1800 208 3399 customersupport@peoplelinkvc.com