



V 1.1 - 102024

## PeopleLink Impact Pro Codec

### KEY FEATURE:

- Sleek design
- 1080P Full HD support
- H.323/SIP support.
- Built-in VPN
- High network security
- Built-in HD MCU (Optional1+5)
- USB microphones support
- USB Recording support
- RSS Live Feed (Optional)


[Watch Video](#)


PeopleLink Video Collaboration Codecs are appliances that provide a robust and flexible scaling platform for creating the ultimate video collaboration experience. One of the most advanced, portable, and feature-rich Codecs available in the market to deliver the ultimate combination of Audio, Video and Data streams to provide an unmatched real-time collaboration. PeopleLink Video Collaboration Codecs get bundled with a wide range of PeopleLink FHD cameras and echo free, acoustically advanced audio devices for forming one of the finest Endpoints to take collaboration from Single huddle rooms to large conference halls. Standards-compliant FHD solution capability offers the most effective video without losing features, even at variable bandwidths. Experience the most extensive and integration-friendly video collaboration engine for connecting your teams spread across different geographies. PeopleLink multi party collaboration Codecs are capable of taking advantage of PeopleLink's comprehensive Solution Management, multi-location visual connectivity, and recording features in a single box to provide a pocket-friendly solution for your collaboration needs.

# Technical Specifications:

## Standards & Protocols

### Multimedia Framework Agreement:

ITU-T H.323, IETF SIP

### Video Codec Protocol:

H.261, H.263, H.263+, H.263++, H.264, H.264 High Profile

### Audio Codec Protocol:

G.711, G.722, G.722.1\*, G.722.1C\*, AAC-LD, G.726, SILK

### Dual Stream Protocol: ITU-T H.239, BFCP

### Other communication protocols:

H.221, H.224, H.225, H.235, H.241, H.245, H.281, H.350, H.460, T.140, DTMF

### Network transport protocol:

TCP/IP, DHCP, SSH, HTTP, HTTPS with SSL / TLS, RTP, RTCP, RFC3261, RFC3264, RFC2190, RFC3984, RFC3407, RFC2833, RFC4585 (RTP/AVPF), SNTP, ARP, RTMP

## Video features

### Active Image Resolution:

1080p, minimum bandwidth 512Kpbs

720p, minimum bandwidth 512Kbps

w448p/4SIF/4CIF, minimum bandwidth 256Kbps

w288p/SIF/CIF, minimum bandwidth 128Kbps

### Active Image Resolution:

**Input :** VGA (640 x 480), SVGA (800 x 600), XGA(1024 x 768), WXGA (1280 x 768), WXGA (1280 x 800), 1280 x 960, SXGA (1280 x 1024), 1360 x 768, 1366 x 768, 1440 x 900, 1600 x 900, 720p (1280 x 720), 1080i (1920 x 1080), 1080p (1920 x 1080)

### Data Content Resolution

**Codec :** 800 x 600, 1024 x 768, 1280 x 1024, 1280 x 720, 1920 x 1080

**Output :** 800 x 600, 1024 x 768, 1280 x 1024, 1280 x 720, 1920 x 1080

### Activity double flow:

Dual streaming 1080p @ 60fps

### Other image properties:

Support PIP, POP and other display modes, three different display

## Bandwidth

IP: 64kbps ~ 8Mbps

## Audio features

**DMIC :** Digital Mic

### Audio features :

Automatic echo cancellation (AEC)

Automatic Gain Control (AGC)

Automatic Noise Suppression (ANS)

Supports lip sync

## Stability and security

### Network adaptability :

Video forward error correction (FEC),

lost packet retransmission (ARQ), etc.

**Security management :** H.235 signaling and media stream encryption (AES-128, AES-256)

TLS and SRTP

Admin Password SSH/HTTPS

**NAT/Firewall Traversal :** H.460 Static NAT

## Interface

**Audio input interface :** 2 x RCA line input, 2 x XLR microphone input, 1 x DMIC, 1 x DVI, 1 x HDMI;

**Audio output interface :** 2 x RCA line output, 2 x HDMI audio output;

### Video input interface :

1 x HDMI, 1 x 3G-SDI

1 x DVI-D

### Video output interface :

3 x HDMI, 1 x 3G-SDI

**USB interface :** 2 x USB2.0 (support USB flash drive, USB microphone, etc.)

**Network Interface :** 2 x RJ45: 10/100/1000 Base-T; for IP networking

**Camera Control Interface :** 2 x RS232

## Meeting Experience Features

**Touch screen control:** PeopleLink Touch Screen Control (Interact AT10T) instead of remote control and image monitoring

**Language :** English

### Contacts and call logs :

1000 local contacts and call records

Presentation sound

Timer switch

Automatic standby and automatic wake-up for incoming calls

DNS SRV support

### Call code

Asymmetric bandwidth

Obtain static NAT address automatically

Picture-in-picture (1/16 screen size), picture-by-picture

Two and three split screen display

## Technical Specifications:

### Special feature

- Internet address book
- Support third-party integrated development API interface
- Built-in MCU
- Support conference control and conference list
- USB microphone access
- USB upgrade, local upgrade and network upgrade
- Infrared transparent transmission
- Conference lock
- PC console
- Vtouch conference control screen
- TR069
- RTMP push and pull live streaming

### General feature

#### Size and weight

**Terminal Dimensions :** 375mm x 428mm x 89mm

**Net weight :** 3.5 Kg

**Gross Weight :** 5.5 Kg

#### Electrical characteristics

**Working frequency :** 50Hz/60H

**Maximum power consumption :** less than 50W

#### Environmental requirements


**Temperature :** 0°C ~ 40°C (working state),  
-40°C ~ 70°C (non-working state)

**Relative humidity :** 10% ~ 80% (working state), 0% ~ 95%  
(non-working state)


**Surrounding noise :** less than 46dBA SPL

**Minimum illumination :** 5lux

Environmental requirements



# Application Scenarios



**Disclaimer:-** Room setup diagrams provided for reference only. Actual room setup and size may vary as per requirements.

## ORDERING INFORMATION:

PeopleLink Impact Pro Codec P2P	: <b>PIP - PIS - COD - P2P</b>
PeopleLink Impact Pro Codec 1+3	: <b>PEP - PIS - COD - 4MP</b>
PeopleLink Impact Pro Codec 1+5	: <b>PEP - PIS - COD - 6MP</b>

## LEARN MORE

For more information on **PeopleLink Impact Pro Codec** [Click Here](#)

## SALES AND INQUIRIES

### Global Headquarters

Q3-A3, 10th Floor Cyber Towers,  
HITEC City, Hyderabad,  
Telangana 500081, **India**  
**Phone:** +91 9100123013  
**Email:** vc@peoplelinkvc.com

### International Contact Numbers

**USA:** +1 669-696-8383  
**Australia:** +61 370 037070  
**France:** +33 6 80 75 26 42  
**Middle East:** +966 5300 19292  
**UK:** +44 20 4571 5454

### Tech Support

**Toll Free:** 1800 208 3399  
customersupport@peoplelinkvc.com