



PeopleLink MCC DSP 200W





PeopleLink DSP is the ultimate choice for High Definition Audio signal processor. The most powerful HD audio available, it delivers full continuous presence meetings with Multi Location Voice conferencing and is ideal for local sound reinforcement. Highly scalable and flexible – PeopleLink's Multichannel Console DSP provides HD voice communications platform. This powerful, fault tolerant solution is ideal for the communication needs of large enterprises as well as service providers looking to offer video conferencing services. Advanced design – This is the most powerful and up to date microphone Mixer, DSP and Amplifier available in the Industry today. It is Compact, Simple and extremely User-friendly allowing you to do Large scale Video Conferencing from a compact audio System.

Product Features:

- Range: Wide operating range of 100 feet
- Power Supply Safety: Power Supply Unit with Short Circuit, Overload and Over Voltage Protection
- **SMT Circuit**: Surface Mount Technology (SMT) Circuit
- **Efficiency**: High efficiency of ~90%
- **Current**: Very low quiescent current. Can run on inverter.
- Circuit: Technology (SMT) Circuit
 Integrated Self-Protection Surface
 Mount
- Frequency lock: Quartz-locked frequency
- Area of application : Classrooms,
 Training Rooms
- Capacity: 50 to 100 seater
- Chassis: 19-Inch chassis 2U (Rack Mountable) DSP with Inbuilt amplifier with wireless microphone System



General Specifications

Wireless Microphone System

Frequency Type: Quartz-locked frequency

Operating Range: 100 Feet

Microphone Options: 2 x Handheld / 1 Handheld +1

headband / 2 x headband Microphones

Frequencies : 5 non interfering frequencies available

Antennas: Soft, Flexible rubberized antennas

Output: Balanced Phoenix and Mixed Unbalanced 1/4"

Outputs

LCD Display: Frequency, Group, Antenna & Channel is

displayed on the LCD in the receiver

Gain Control: Separate gain controls for both the

channels

Microphone Frequency Response: 80 Hz-18KHz

Microphone Type: UHF

Amplifier

Power Output @ 8 ohms: 2 X100W, Vcc= 24V DC

Minimum Impedance: 8 ohms @100W

Frequency Response: 20 Hz-20,000Hz

Operating Supply voltage: 8 V to 24 V

Type: Class D (Digital)

Digital Signal Processor

Frequency Range : 30 Hz. to 16KHz.

Automatic Echo Cancellation: Yes

Automatic Gain Control: Yes

Dynamic Noise Reduction: Yes

Noise Supression: Yes

Full Duplex: Yes

Interface

Input: Built-In 1 x Handheld, 1 x Headband

Microphone

Unbalanced MIC Input: 1x 6.5mm phono jack with

gain controller

Balanced 48v / 12v phantom MIC inputs : 2 x Phoenix

ports with separate gain controller

Line input: 1 x 2RCA

Line Output: 1 x 2RCA

USB Interface for PC connectivity: 1 x USB 2.0

RS-232 for controlling: 1x RS-232 audio controlling

Miscellaneous

Power Supply Unit (PSU): Power Supply Unit with Short Circuit, Overload and Over Voltage Protection

Application : Classrooms, Training Rooms

Capacity: 50 to 100 Seater

Shape of the room : Any

Packaging Information

Components: 19 inch chassis 2U (Rack Mountable)

with Inbuilt DSP

Package Includes: Inbuilt Package Includes People Link Multi Channel Console DSP with built-in-Amplifier, Wireless Handheld Microphone, Wireless Headband Microphone, USB 2.0x1,Cable, Stereo to Microphone, 2


RCA Cable x 2, 50W Speakers x 2







Device Set-up







Disclaimer:- Room setup diagrams provided for reference only. Actual room setup and size may vary as per requirements.



Ordering Information

PeopleLink MCC AIO DSP 200W

: PCU-MCC-DSP-AIO - 200W

LEARN MORE

For more information on AIO DSP 200W Click Here

SALES AND INQUIRIES

Global Headquarters

Q3-A3, 10th Floor Cyber Towers, HITEC City, Hyderabad, Telangana 500081, **India** Phone: +91 9100123013 Email: vc@peoplelinkvc.com

International Contact Numbers

USA: +1 669-696-8383 Australia: +61 370 037070 France: +33 6 80 75 26 42 Middle East: +966 5300 19292 UK: +44 20 4571 5454

UAE: +971 4 3339082 Canada: +1 647-945-7373 Malaysia: +(6)018-2872188 New Zealand: +64-9-802-4666 Africa: +254 107 529 656

Tech Support

Toll Free: 1800 208 3399 customersupport@peoplelinkvc.com