

V 1.1 - 122024



PeopleLink Interactive Display R Series 65 inch


[Watch Video](#)


Redefine Smarter Collaboration with PeopleLink Interactive Display R65

Let the versatile 4K UHD interactive display bring more collaboration and student engagement to your classroom. With a button, you can turn the display into a digital whiteboard, share files in one touch, and use your favorite software. PeopleLink R65 Interactive display works in your world and lets you interact your way.

Key Features

- Zero bonding technology, low parallax writing and wider viewing angles
- 4mm anti-glare tempered glass lap
- 4K Ultra HD display, support full channel 4K UI display
- Front panel USB 3.0 x 2, with 6 buttons
- Support Screen Mirroring
- High precision IR touch makes the user write more smoothly
- Support dual pens with different color displays, which makes teamwork easier
- One network support, Android and OPS are 100 Gigabit networks
- Support for network sharing
- High level welcome application, enriching the live interactive experience with great fun
- Split whiteboard, parallel tasks and wider scenes
- New hover ball mode for quick customization of features
- Eye protection, lock screen, touch lock and other tools
- Support for multi-user functionality

- **Superior Touch Experience**

With PeopleLink R65 advance technology, users can annotate with a writing stylus or fingers which is as natural as writing on papers.

- **Interaction made Easy**

PeopleLink R65 Interactive display brings efficiency to your classes and teams so you can interact with ease, anytime. With a lightweight slim frame design, Windows system and built-in OS support, embedded tools and a personalized user interface, it's the perfect solution to seamless collaboration in school and in the office.

- **Interact with the Whole Group**

PeopleLink R65 Interactive display series supports up to 20 points of touch, allowing multiple users to interact at the same time. With smooth and responsive touch, anyone can take notes, write and draw on the screen, making the classroom a truly collaborative space.

- **Customize the Interface to meet your needs**

Whether you need a display for your classroom or conference room, the PeopleLink R65 Interactive display lets you easily change the screen theme and personalize the user interface on your built-in operating system. Keep the home screen simple while giving your team quick access to any tools they might need.

General Specifications

Display Parameters

Size : 65"

Visual ratio : 16:9

Max visual area : 1429(H) × 804 (V)mm

Resolution : 3840 (H) × 2160 (V)

Pixel pitch : 0.372 × 0.372mm

Frequency : 60Hz

Display colors : 1.07B (10bit)

Color gamut (Typ) : 72%

Contrast ratio (Typ) : 1200:1

Dynamic contrast ratio : 30,000:1

Viewing angle : 178°(H/V)

Back light source : DLED

Brightness : Upto 450 nits

Life span : ≥50000hrs

Speakers

Soundtrack : 2.0

Power : 2 × 20W

Touch Specification

Touch mode : Infrared identification

Touch points : 20 points touch

Minimum identifier : 2mm (±1mm)

Input mode / Writing display : Opaque object (finger, pen, etc.)

Response time : ≤5ms

Touch accuracy : ±1mm

Writing height : ≤3mm

Output coordinates : 32767 (W) × 32767(D)

Surface hardness : 9 Mohs

General Specifications

System

System version : Android 14.0
Working frequency : 1.2GHZ and 1.5GHZ
CPU : Octa core A55
GPU : Quad-core MaliG52
RAM : 8GB
ROM : 128GB
OSD : English (Supports all major Indian languages)

Bluetooth

Bluetooth version : 5.2
Operation frequency : 2.4GHz
Operation distance : 0~10m
Remark : Built-in Bluetooth

Wi-Fi

Version : IEEE 802.11 a/b/g/n/ac/ax
Operation frequency : 2.4GHz/5GHz
Operation distance : 0~10m
Remark ; Built - inWi-Fi mode

Power Parameters

Voltage : 100-240V~ 50/60Hz 4A
Max power consumption : 210W
Standby power consumption : ≤0.5W

Size and Weight

Bare dimension : 1484.60 × 909.88 × 87.2mm
Packing dimension : 1630 × 220 × 1050mm
Machine + wall mount thickness : 123.31mm
VESA hole site : 500 × 400mm
Wall mounting screw specifications : M8 × 25mm
Net weight ; 41.20 KG
Gross Weight : 54.00 KG

Front Interface

USB 3.0 : 2

Keys : Power/Homepage/Screen down/Record/Touch lock/Setting

Onboard Interface

1 x TF Card supports (64GB,128GB, 256GB Up to 1 TB,
1 x USB 3.0, 1 x USB 2.0, 1 x TOUCH Out, 2 x HDMI In,
1 x VGA, 1 x AUDIO IN/AV In, 1 x RS232, 1 x RJ45 IN,
1 x Earphone, 1 x Coax

Optional Interfaces

1 x HDMI Out, 1 x DP In, 1 x RJ45 Out, 1 x Mic In,

OPS

CPU : Intel® Core™ i5/i7, 8th/10th/12th Gen,
Octa Core Processor

Memory : 8GB RAM / 16GB DDR4

Storage: 256GB SSD / 512 GB/ HDD iTB (Optional)

Interfaces : 6 x USB3.0 Type-A, 1x USB Type-C, 1xRJ45
10/100/1000M , 1xHDMI1.4 out, Max.4K/30Hz,
1 x DP out, 1 x 3.5mm Line out, 1 x 3.5mm Mic in,
2 x WIFI ANT, 1 x Power button,

Accessories

1 x Power cord, 1 x HDMI cable, 1 x Touch cable,
1 x USB cable, 2 x Writing Pen, 1 x Wall mount,
1 x Operational Manual

Environmental factors

Working temperature : 0°C~40°C

Working humidity : 10%~90%RH

Storage temperature : -20°C~60°C

Storage humidity : 10%~90%RH

Working elevation : <5000m


Optional modules

OPS module dimension


OPS size (120mm x 180mm x 30mm)

OPS size (195mm x 180mm x 42mm)

Application Scenarios



Disclaimer:- Room setup diagrams provided for reference only. Actual room setup and size may vary as per requirements.



Ordering Information

R65S Standard (4+32GB)	: PDS-ICB-RX16
R65SH Standard (4+32GB) with HDMI-Out Port	: PDS-ICB-RX17
R65E Expanded (8+128GB)	: PDS-ICB-RX18
R65EH Expanded (8+128GB) with HDMI-Out Port	: PDS-ICB-RX19

LEARN MORE

For more information on **Interactive Display 65 inch** [Click Here](#)

SALES AND INQUIRIES

Global Headquarters

Q3-A3, 10th Floor Cyber Towers,
HITEC City, Hyderabad, Telangana
500081, **India**
Phone: +91 9100123013
Email: vc@peoplelinkvc.com

International Contact Numbers

USA: +1 669-696-8383
Australia: +61 370 037070
France: +33 6 80 75 26 42
Middle East: +966 530019292
UK: +44 20 4571 5454

Tech Support

Toll Free: 1800 208 3399
customersupport@peoplelinkvc.com