




PeopleLink

Active LED 2.5



- PeopleLink's Active LED Panel – a pinnacle of performance in commercial-grade, direct-view LED displays.
- With pixel pitches catering to diverse needs—from high-resolution cinema video walls to expansive sports venue boards and collaborative touch-based displays, our technology transforms spaces.
- Elevate your conference halls, meeting rooms, and indoor events with a PeopleLink Video Wall.
- Our commitment lies in pioneering technology that not only gains popularity but excels in design, resolution, sizes, and shapes tailored to your preferred location and installation area, ensuring an extraordinary visual experience for your visitors.

PeopleLink Active LED 2.5



1 Using high-quality LED,
high brightness utilization



2 High contrast



3 Lightweight
and easy to
disassemble



4 Single lamp
maintenance
Low cost

MDL

Pitch(mm)	:	2.5
LED Model	:	SMD2020
LED Type	:	Copper wire
Resolution	:	128*64
Size±Tolerance (mm×mm×mm)	:	319.9±0.1*159.9±0.1*14.2±0.2
Weight±Tolerance (kg)	:	0.42±0.05
Flatness (mm)	:	< 0.2
Pixel density(dot/m²)	:	160000

Optical Parameters

Brightness(cd/m²)	:	≥500
Color temperature(k)	:	3000~15000 (Adjustable)
Horizontal Angle of view(°)	:	≥150
Vertical Angle of view(°)	:	≥130
Viewing distance	:	≥2.5 Meter

Electrical Parameters

Max power consumption of a module	:	≤20W
Average power consumption of a module	:	≤130W/m ²
Maximum active power consumption	:	≤390W/m ²
Working voltage(V)	:	5
Signal input interface type	:	HUB75

Processing performance

Scanning method	:	32
frame frequency(Hz)	:	50/60
refresh rate(Hz)	:	3840
Drive mode	:	Constant current driver
Gray(bit)	:	13

Running parameters

Continuous working hours	:	≥7*24hrs, (support continuous uninterrupted display)
Average time without failures	:	≥5000hrs
Discrete runaway point	:	≤0.0001, 0 (at the factory)
Continuous runaway point	:	0
Blind spot rate	:	≤0.0001, 0 (at the factory)
LED Lifetime, Typical(hrs)	:	30000
Operating temperature(°C)	:	-20+40
Storage temperature(°C)	:	-20+60
Operating humidity(RH)	:	10%-60% (No condensation)
Storage humidity(RH)	:	10%-65%(No condensation)

Protection level

Ingress Protection	:	IP30
---------------------------	---	------

Ordering Information

Part code

PeopleLink ActiveLED 2.5PP Video LED Modules	:	PDS-TP-15-T
PeopleLink ActiveLED Video Wall Cabinet Unit	:	PPL-ALD-CU

SALES AND INQUIRIES

Global Headquarters

Q3-A3, 10th Floor Cyber Towers,
HITEC City, Hyderabad,
Telangana 500081, **India**
Phone: +91 9100123013
Email: vc@peoplelinkvc.com

International Contact Numbers

USA: +1 669-696-8383
Australia: +61 370 037070
France: +33 6 80 75 26 42
Middle East: +966 5300 19292
UK: +44 20 4571 5454

UAE: +971 4 3339082
Canada: +1 647-945-7373
Malaysia: +(6)018-2872188
New Zealand: +64-9-802-4666
Africa: +254 107 529 656

Tech Support

Toll Free: 1800 208 3399
customersupport@peoplelinkvc.com

Follow us:       www.peoplelinkvc.com/social-presence

DISCLAIMER: PeopleLink Unified Communications Pvt. Ltd., All rights reserved. All third party trademarks / products mentioned (if any) are the property of their respective owners. Product images are for illustration purpose only. Actual product may vary due to product enhancements. All specifications are subject to change without notice; system specifics may vary.

PeopleLink Public Document | PeopleLink Unified Communications Pvt. Ltd. | ISO 9001:2015 & ISO/IEC 27001:2013 Certified Company.