



## 4K Videobar with PTZ Camera



The Video Bar with PTZ Camera is designed for seamless professional communication, featuring exceptional video clarity at various frame rates and an advanced audio system with six built-in beamforming microphones and two full-range speakers. It boasts a CMOS sensor with 8.29 million effective pixels, mechanical PTZ capabilities with up to 255 preset positions, and automatic focus with digital noise reduction for crystal-clear images and sound. Ideal for boardrooms and classrooms, it offers flexible connectivity options including HDMI, USB 3.0, RJ45, and Bluetooth 5.0, making it easily scalable to various setups. Pricing details will be determined based on configuration and additional features.

## Key Features

- **4K Resolution:** 4K technology in this camera ensures high-definition video quality, meeting market demand for clear visuals in professional settings.
- **Enhanced Audio Technology:** With advanced beamforming microphones, the camera excels in noise cancellation and audio clarity, a trend driven by the rise in remote work and virtual meetings.
- **Automated Features:** The inclusion of auto-focus and digital noise reduction aligns with the trend toward user-friendly, automated solutions that enhance user experience without manual adjustments.
- **Flexible Connectivity:** Offering multiple connection options, including USB 3.0 and Bluetooth, meets the increasing need for versatile integration in various environments, reflecting current preferences for adaptability.
- **Mechanical PTZ Capabilities:** The camera's mechanical pan-tilt-zoom functionality addresses the growing demand for dynamic video conferencing solutions, allowing for more engaging presentations and interactions.

## General Specifications

### Close-up camera parameters

**Video Resolution :** 4K@30/25fps, 1080P@30/25fps, 720P@30/25fps, etc.

**Sensor :** CMOS, 1/2.5 inches, 8.29 million effective pixels (3840 x 2160)

**Lens Focal Length :** 12X, f=4.4~51.1mm, F1.8~2.6

**Horizontal Field of View :** 70.1° ~7.4°

**Horizontal Rotation Range :** -90° ~ +90°

**Horizontal Rotation Speed Range :** 1.7° ~ 76° /s

**Vertical Field of View :** 40.7° ~4.2°

**Vertical Rotation Range :** 23° ~ +23°

**Vertical Rotation Speed Range :** 0.5° ~ 15° /s

**Horizontal and Vertical Flip :** Support

**Image Freeze :** Support

**Number of Preset Positions :** 255

**Preset Position Accuracy :** 0.1°

**Mechanical PTZ :** Support

**Auto Focus AF :** Support

**White Balance :** Automatic, Indoor, Outdoor, One-touch, Manual

**BLC :** Support

**Digital Noise Reduction :** 2D & 3D Noise Reduction

**Signal-to-Noise Ratio :** >=55dB

### Audio

**Speaker :** 2 full-range speakers

**Built-in Microphone :** 6 analog silicon microphones, beamforming microphones, pickup distance 8 meters

**Audio 3A Algorithm :** Support

**Sampling Rate :** Mic 32K, speaker 48K

**Extended MIC :** Support

### Panoramic camera parameters

**Video Resolution :** 4K@30/25fps, 1080P@30/25fps,

720P@30/25fps, 640 X 360@30/25fps

**Sensor :** CMOS, 1/2.5 inches, 8.29 million effective pixels (3840\*2160)

**Optical Lens :**

- **Fixed-focus lens focal length :** 2.8mm
- **DFOV :** 117°
- **HFOV :** 108°
- **VFOV :** 74°

**Mechanical PTZ :** Not support

**EPTZ :** Support

**White Balance :** Automatic

**BLC :** Support

**Digital Noise Reduction :** 2D & 3D Noise Reduction

**Signal-to-Noise Ratio :** ≥55dB

### General specifications

**Security :** Kingston anti-theft lock socket

**Operating/Stored Temperature :**

0° C ~ 40° C / -40° C ~ 60° C

**Dimensions (L x H x D) :**

- **Without bracket:** 600mm x 127.1mm x 182.1mm
- **With bracket:** 600mm x 127.1mm x 217.1mm

## General Specifications

### USB features

#### Supported Operating Systems :

- Windows® 7 (supports 1080p and below only),
- Windows 8.1, Windows 10 or higher
- Mac OS™ 10.10 or higher
- Google™ Chromebook™ Version 29.0.1547.70 or higher
- Linux (UVC support required)

#### Hardware Requirements :

- 2.4 GHz Intel® Core 2 Duo processor or higher
- 2 GB RAM or higher
- USB 2.0 port (4K requires USB 3.0)

**Connection Type :** USB3.0, backward compatible with USB2.0

**Color Space/Compression :** MJPEG/YUY2

#### USB Video Communication Protocol :

UVC 1.1、UAC 1.0

**UVC PTZ Control :** Support

### Input and output interface

**USB 3.0 :** 1 × USB 3.0, type-C, Support audio/video transmission and firmware upgrade

**HDMI :** 1 × HDMI, supports local video display

**USB 2.0 :** 1 channel, USB 2.0, type-A, female, connect to USB wired expansion microphone

**Network Port :** 1 × RJ45, connect to network port expansion microphone, support POE power supply  
1 × RJ45, 10/100M adaptive Ethernet port, supports network transmission of audio and video

**Power Interface :** DC 12V

**Bluetooth :** Bluetooth 5.0, supports Bluetooth connection to mobile phones, laptops and other devices, and transmits audio

**Wifi :** Wifi 5, supports BYOM wireless transmission and BYOD wireless screen projection (extra screen projection device is required)

**Remote Control :** Support

## Ordering Information

4K Videobar with PTZ Camera :

### SALES AND INQUIRIES

#### Global Headquarters

Q3-A3, 10th Floor Cyber Towers,  
HITEC City, Hyderabad, Telangana  
500081, **India**

**Phone:** +91 9100123013

Email: [vc@peoplelinkvc.com](mailto:vc@peoplelinkvc.com)

#### International Contact Numbers

**USA:** +1 669-696-8383

**Australia:** +61 370 037070

**France:** +33 6 80 75 26 42

**Middle East:** +966 5300 19292

**UK:** +44 20 4571 5454

**UAE:** +971 4 3339082

**Canada:** +1 647-945-7373

**Malaysia:** +(6)018-2872188

**New Zealand:** +64-9-802-4666

**Africa:** +254 107 529 656

#### Tech Support

**Toll Free: 1800 208 3399**

[customersupport@peoplelinkvc.com](mailto:customersupport@peoplelinkvc.com)