



## PeopleLink Impact Digital Array Microphone



The **PeopleLink Impact Digital Array Microphone** features a high SNR ring microphone array, enabling clear long-distance pickup and allowing speakers to move freely without constraints. Utilizing blind beamforming technology, it offers precise positioning and voice enhancement, improving anti-interference in adaptive sound environments. Equipped with smart audio algorithms, the microphone delivers clear, natural sound through advanced features like voice tracking, intelligent noise reduction, echo cancellation, automatic gain control, and de-reverberation. With PoE cascading, it ensures even sound coverage for large conference rooms, and its flexible design allows for seamless integration into various environments, supporting easy installation and customization.

### Key Features

- Digital Array Microphone
- Blind Beamforming; Automatic Alignment to Speaker
- Smart Audio Algorithms; Clear Natural Sound
- PoE Cascading; Even Coverage of Conference Room Pickup
- Standard Interface, Plug and Play

## General Specifications

### Audio Parameters

**Microphone Type :** Digital Array Microphone

**Microphone Array :** 6 omnidirectional microphones form a circular array for 360 degree omnidirectional pickup

**Pickup Distance :** 3m

**Sensitivity :** -38 dBFS

**Signal Noise Ratio :** 65 dB(A)

**Frequency Response :** 50Hz - 16kHz

**Sampling Rate :** 32K sampling, high-definition broadband audio

**Automatic Echo Cancellation (AEC) :** Support

**Automatic Noise Suppression (ANS) :** Support

**Automatic Gain Control (AGC) :** Support

### Cascade Function

Cascade Mode : PoE network cable

### Hardware I/O

**Network Interface :** RJ45 up and down cascade network Interface

**USB Interface :** USB audio interface (Type-C), support UAC1.0 protocol, audio data communication, software upgrade and parameter configuration

**Analog Audio :** AUX1 , AUX2 line audio input and output

### Generic Spec

**Power Input :** PoE cascade 48V power supply, support IEEE 802.3 at standard / USB 5V 500mA (single)


**System :** Windows / Mac / Linux

**Installation Method :** Desktop, lifting, wall mounted, ceiling mounted


**Dimension :** 170 mm × H 40 mm

**Net Weight :** 370 g

## Interface Diagram



## Application Scenarios



**Disclaimer:-** Room setup diagrams provided for reference only. Actual room setup and size may vary as per requirements.

## Ordering Information

PeopleLink Impact Digital Array Microphone

:

### SALES AND INQUIRIES

#### Global Headquarters

Q3-A3, 10th Floor Cyber Towers,  
HITEC City, Hyderabad, Telangana  
500081, India

Phone: +91 9100123013

Email: [vc@peoplelinkvc.com](mailto:vc@peoplelinkvc.com)

#### International Contact Numbers

**USA:** +1 669-696-8383

**Australia:** +61 370 037070

**France:** +33 6 80 75 26 42

**Middle East:** +966 5300 19292

**UK:** +44 20 4571 5454

**UAE:** +971 4 3339082

**Canada:** +1 647-945-7373

**Malaysia:** +(6)018-2872188

**New Zealand:** +64-9-802-4666

**Africa:** +254 107 529 656

#### Tech Support

**Toll Free: 1800 208 3399**

[customersupport@peoplelinkvc.com](mailto:customersupport@peoplelinkvc.com)