



V.1.0 - 102024

## PeopleLink Interactive Podium



The **PeopleLink Interactive Podium** is designed to operate efficiently across a variety of environmental conditions. It supports a storage humidity range of 10% to 90% non-condensing and a working humidity range of 20% to 85% non-condensing, ensuring optimal performance in diverse settings. With a storage temperature tolerance from  $-10^{\circ}\text{C}$  to  $+60^{\circ}\text{C}$  and a working temperature range of  $0^{\circ}\text{C}$  to  $+40^{\circ}\text{C}$ , this lectern is versatile for different climates. It can function effectively at altitudes up to 5000 meters and offers an impressive usage time of 18 hours per day over a week, making it suitable for extended use in various environments.

## Key Features

- **High-Performance Processing:**  
Equipped with an 8-core processing chip and the latest Android 12.0 system for smooth operation and quick software response.
- **Large 27" 4K Display:**  
Features a high-definition 27" screen with 3840x2160 resolution for clear visuals, enhancing the viewing experience.
- **Multi-Touch Support:**  
Supports up to 20-point capacitive touch for accurate and responsive interaction, ideal for engaging presentations.
- **Versatile Connectivity:**  
Offers multiple connectivity options including HDMI, USB, and TYPE-C for seamless integration with other devices.
- **Electric Lifting System:**  
Includes an electric lifting mechanism to accommodate different speaker heights and preferences, ensuring ergonomic usage..

# General Specifications

Item	Parameter
LCD Size	: 27"
Backlight Type (Backlight Type)	: 3840x2160(pixels)
Brightness	: 400 cd/m <sup>2</sup>
Contrast Ratio	: 1000:1
Response Time	: 14ms
Pixel Pitch (mm)	: 0.1554mm(H)×0.1554mm(V)
Viewing Angle	: 178°(H)/178°(V)
Life Time	: 30,000 hrs (min.)
Color Gamut (X% NTSC)	: 72% (typ.)
View Area (mm)	: 596.736mm×335.664mm
Display Colors	: 1.07B colors
System version (OS)	: Android12
Internal cache capacity (RAM)	: 8GB DDR4
Internal storage capacity (ROM)	: 64GB (Standard 64GB)
Voltage (Power Requirements)	: DC 20V/5A
Maximum power (Power Consumption)	: 100W
Standby power (Standby Consumption)	: 0.5W
Wi-Fi Standard	: IEEE 802.11a/b/g/n/ac
Frequency (Operating Frequency)	: 2.4GHz/5GHz
Bluetooth	: 2.1+EDR / 4.2 / 5.2
HDMI IN	: Version: HDMI2.1×1 Up to 3840×2160@60Hz
Type-C OUT	: Max Resolution: 3840x2160@60Hz Version DP1.2
USB-A	: ×2 Support images, music, video file playback. Upgrade are not supported Interface: USB3.0 Type-A
HDMI OUT	: All signal can be looped-out ×1 Max Resolution: 3840x2160@60Hz Version HDMI2.1 (TMDS)



- Microphone switch, the default is to open
- Lift control switch, starts when pressed, stops when released
- Stylus, No need to match , write directly

## General Specifications

---

<b>RJ45</b>	: 10M/100M/1000M Base-T self-adaptive ×1
<b>Ethernet Interface</b>	: RJ45
<b>TYPE-C IN (power interface)</b>	: ×1 Power supply (Adapter) DC 20V/5A
<b>Bare machine dimensions (W×D×H)</b>	: 775.6mm * 526mm * 1118mm
<b>Base Elevation</b>	: Support
<b>Base Lifting/Rotation Adjustment</b>	: Support
<b>Accessories</b>	
<b>Stylus</b>	: 1
<b>Adapter</b>	: 1
<b>Gooseneck microphone</b>	: 2
<b>5m HDMI Cable</b>	: 1
<b>1.8m Type-C Cable</b>	: 1
<b>screen sharing dongle</b>	: 1 (Optional)
<b>Qualified Certificate Label</b>	: 1
<b>Instructions</b>	: 1
<b>Warranty Card</b>	: 1
<b>Environment</b>	
<b>Storage humidity</b>	: 10% ~ 90% non-condensing
<b>Working humidity</b>	: 20% ~ 85% non-condensing
<b>Storage temperature</b>	: -10 ~ +60
<b>Working temperature</b>	: 0 ~ +40
<b>Usage time</b>	: 16 hours x 7 days

## Ordering Information

---

PeopleLink Interactive Podium :

### SALES AND INQUIRIES

---

#### Global Headquarters

Q3-A3, 10th Floor Cyber Towers,  
HITEC City, Hyderabad,  
Telangana 500081, **India**  
**Phone:** +91 9100123013  
**Email:** [vc@peoplelinkvc.com](mailto:vc@peoplelinkvc.com)

#### International Contact Numbers

**USA:** +1 669-696-8383  
**Australia:** +61 370 037070  
**France:** +33 6 80 75 26 42  
**Middle East:** +966 5300 19292  
**UK:** +44 20 4571 5454

#### Tech Support

**Toll Free:** 1800 208 3399  
[customersupport@peoplelinkvc.com](mailto:customersupport@peoplelinkvc.com)